FURBISH CHEMICAL & SUPPLY CO. Of ALASKA, INC.
501 Raspberry Road
Anchorage, Alaska 99518-1569
Phone (907) 344-4184 Fax (907) 344-5919

SUPER BLUE

HEAVY DUTY CLEANER & DEGREASER

DESCRIPTION: This product is a concentrate heavy duty degreaser for industrial use. It is a blend of water soluble solvents, surface active detergents, water softeners, corrosion inhibitors, and alkaline builders. It's concentrated powerful ingredients will clean virtually everything from painted surfaces to greasy metal parts. Used at full strength for a light oil parts dip to 60-1 dilution for cleaning Venetian blinds, light fixtures, painted wood work and many other light duty jobs. The product is designed to be fast acting with maximum safety to materials used upon, and to user when used in recommended dilutions.

ADVANTAGES:

No flash point.
Contains rust inhibitors.
Versatile.
Apply with sprayers, pressure washers, by brush, rag or in steam cleaners.
Concentrated, cuts costs.
Chemically dissolves oil and grease.
Removes soap scum.
Use in cold or hot water; hard or soft.
Authorized by USDA for use in Federally Inspected meat and poultry plants.
Cuts through grease, grime, oil, dye, wax, rust, exhaust smoke, scum and dirt.

RECOMMENDED USES: This degreaser is recommended for use in schools, restaurants, machine shops, industrial plants, food processing plants, meat packing plants hotels, motels, automotive, truck, and bus maintenance shops. It will clean concrete floors, walls, vents, hoods, ovens, grills, chrome, stainless steel, painted woodwork, fiberglass, Venetian blinds, light fixtures, machinery, equipment, white wall tires, vans and food processing equipment. Use it as a light duty parts dip, steam cleaner, and a pressure washer cleaner.

NOTICE:
The information contained herein, is to the best of our knowledge and belief, accurate. Since the conditions of handling and use are beyond our control, we make no guarantee of results. We assume no liability for damages or penalties resulting from our suggestions or recommendations, nor are these to be taken as a license to operate under, or recommendations to infringe, any patent.

DIRECTIONS FOR USE:

FOR CLEANING GREASE FILTERS, DUCTS, REFUSE CONTAINERS OR OTHER TOUGH GREASE REMOVAL JOBS, INCLUDING WAX REMOVAL: Dilute 1 part product with 8 parts hot or cold water. (Spray on, wipe on, mop on, or dip.) Rinse with clear water.

FOR MOP, SPONGE OR SPRAY APPLICATION TO FLOORS, TRUCK AND BUS CHASSIS, AND OTHER METAL SURFACES: Dilute 1 part product with 12 parts hot or cold water). Rinse after cleaning with clear water.

FOR GENERAL OVERALL CLEANING OF PAINTED WALLS AND WOODWORK:
Dilute 1 part cleaner with 24 parts hot or cold water 3/4 cup per gallon of water). Spray on surface, then wipe with damp sponge, then wring out sponge and wipe clean. No rinsing required.

FLOORS: Dilute one to two ounces of cleaner per gallon of water. Wet floor with cleaning solution, allow to stand for a few minutes to allow lifting action to pick up all dirt. Pick up solution with wet vac or mop. ALWAYS RINSE BEFORE WAXING.
NOTE: Do not use for daily maintenance of floors unless used in 1 to 100 dilutions.

LAUNDRY: Use full strength for pre-spot and collars. Add ½ cup to wash load as a detergent booster.

CONCRETE FLOORS; For greasy build up on concrete floors, dilute 1 part cleaner to 10 parts water, machine or hand scrub with wire brush and rinse well.

FOR STRIPPING SEALERS: Use a dilution of 1 part cleaner to 10 parts water. Machine scrub with wire brush and rinse well.

STEAM CLEANING: Mix 20 parts water to 1 part cleaner (6 oz. to 1 gallon water).

PRESSURE WASHER: Mix 10 parts water to 1 part cleaner (12 oz. to 1 gallon water).

CAUTION: Contains butyl cellosolve, may be harmful if swallowed. Do not use in undiluted state. Protect skin and eyes from contact with undiluted product.

SPECIFICATIONS;.

Color.....Blue
Fragrance.....Lemon
Residual Odor.....None
Residual Film.....None after wiping dry
Type of Surfactant..... Medium foamer, biodegradable, free rinsing
Type of Soap.....None
Solvents.....Butyl Cellosolve 10%
Other dirt, grease and soil cutting solvents are present
Flash Point.....None
Viscosity at 77F.....A-1 (Gardner Holdt)
Specific Gravity.....1.050±0.005
pH at 77F.....12.2
Solids.....9.5%
Active Ingredients.....20%
Weight Per Gallon.....8.75
Stability.....Excellent
Shelf Life.....Excellent

CAUTION

KEEP OUT OF REACH OF CHILDREN
DO NOT TAKE INTERNALLY
PROTECT FROM FREEZING